

ORIGINAL



Republic of the Philippines  
 Department of Agriculture  
**AGRICULTURAL TRAINING INSTITUTE**  
 ATI Building, Elliptical Road, Diliman, Quezon City, Metro Manila 1100  
 Tel. Nos. (63-2) 8929-8541 to 49 & 8928-7397 Fax No. (63-2) 8920-9792  
 Email: ati\_director@ati.da.gov.ph & ati\_director@yahoo.com  
 URL: http://www.ati.da.gov.ph; www.e-extension.gov.ph

**PURCHASE ORDER**

SUPPLIER: **RIELOU GENERAL MERCHANDISE**  
 ADDRESS: BLK 1 & 2 SOCORRO AVENUE, BUENSUCESO  
 HOMES III PARANAQUE CITY


P.O. No.: 2021-12-265  
 DATE: Dec 22, 2021  
 MODE OF PROCUREMENT: NP-SMALL VALUE  
 PROCUREMENT

TIN:  
 Gentlemen:

Please furnish this Office the following article(s) subject to the terms and conditions contained herein.

Place of Delivery: ATI, Diliman, Quezon City  
 Delivery Terms: 15 WORKING DAYS  
 Date of Delivery: LLDAP  
 Payment Term:

STOCK NO.	UNIT	DESCRIPTION	QTY	UNIT COST	TOTAL COST
		<b>OFFICE EQUIPMENT</b> <b>LOT 1</b> <b>Office Studio setup package for production of videos and online trainings</b>  <b>2 Dimmable LED bar kit (2 pcs)</b> 30w Dimmable LED Bar Daylight 5500k with 190cm / 6ft Stand with carrying bag <b>2- 300w photo/video light (for the rail system)</b> 5600 ± 200K daylight CCT AC power supply 300W COB LED light 5600 ± 200K daylight CCT CRI: ≥95, TLCI: ≥95 Support 2.4G remote control, Mobile APP contr 16 Channels A/B/C/D/E 5 groups LCD display with backlight "Triple silent cooling fan S-type mount compatible with bowens mount" <b>1 Parabolic softbox</b> Bowens mount 74 cm depth with diffuser bowens mount adapter ring reflective liner parabolic shape <b>1 Octagonal softbox</b> Width 180cm x Max Height 200cm made with flat, no-creased fabric dust-proof metal casing with 2 hanging rings and mounting holes self-lock and manual release 100% polyester fabric <b>6 Background cloth (set)</b> non-woven seamless cloth 95-100 gsm thickness 1.6 meters x 3 meters size Green, Black, White, Gray, Blue and Red <b>1 Roll-up chroma green screen</b> Wrinkle Resistant Oxford Chroma Green Material Aluminum Housing 150cm x 200cm Maximum Height Hydraulic Assisted Open Screen Size: 59 × 82.67 inches / 150 × 210 centimeters MAX Retracted Size: 61 × 4.3 × 4.7 inches / 156 × 11 × 12 centimeters Weight: 8.75 kilograms <b>4 parabolic shoot-thru umbrella</b> fiber glass ribs white diffuser stainless steel main rod 130 cm (size when open); depth 47 cm	1	₱ 594,580.00	₱ 594,580.00



STOCK NO.	UNIT	DESCRIPTION	QTY	UNIT COST	TOTAL COST
		<p><b>2 C-stand (for lights)</b>  2.5" Grip Head and 40" Arm  Chrome-plated Construction  3 Sections, 2 Risers  Detachable Base</p> <p><b>4 Light stands</b>  aluminum material  Folded Length: 104cm  Max Height: 300 cm  Tube Diameters: 35/30/25mm  Tip: 1/4" screw or 3/8" screw</p> <p><b>2 V860IIN TTL Li-Ion flash kit for Nikon</b>  2.4GHz X wireless radio system  range: 328 feet  32 channels, 3 groups  zoom range 20-200 mm  wide angle lens support up to 14 mm  flash head tilt -7 to 90°  flash head rotation 180° left and right  AF assist up to 33 feet  multi flash, high-speed sync, 1st and 2nd curtain sync, flash exposure compensation  11.1V, 2000mAh Li-ion polymer battery pack  hot shoe and wireless trigger support</p> <p><b>2 Wireless flash trigger transmitter for Nikon</b>  Works with X Wireless Radio System  Compatible with Nikon i-TTL  Frequency: 2.4 GHz  Range: 328'  32 Channels; 5 Groups  Backlit LCD Screen; Sync Delay Settings  Exposure Compensation &amp; Exposure Lock  Ratio Flash Mode; High-Speed Sync  Hot Shoe and PC Sync Terminal  Micro-USB Ports for Firmware Updates</p> <p><b>2 Wireless flash trigger receiver for Nikon</b>  Works with X Wireless Radio System  Compatible with Nikon i-TTL  Frequency: 2.4 GHz  Range: 328'  32 Channels; 5 Groups  Backlit LCD Screen; Sync Delay Settings  Exposure Compensation &amp; Exposure Lock  Ratio Flash Mode; High-Speed Sync  Hot Shoe and PC Sync Terminal  Micro-USB Ports for Firmware Updates</p>			

STOCK NO.	UNIT	DESCRIPTION	QTY	UNIT COST	TOTAL COST
		<p><b>2 power surge protector, power conditioner</b>  10 outlets  2000W power  with digital power supply regulator and voltage readout  1 U rack mount  with USB port  4.25 x 20.75 x 12.75 inches</p> <p><b>2 microphone pre-amplifier</b>  High-voltage Class A 12AX7 vacuum-tube mic/instrument preamplifier  Gain, Tube Drive, HP filter, -20 dB pad, phantom power, polarity reverse 3-band EQ features variable-Q on mid-band w/ peak/shelving on high- and low-bands</p> <p>Variable VCA compressor with Auto Attack/Release and Soft/Hard Knee  3-band EQ with parametric mid and semi-parametric, shelving/peak low and high bands  Instrument, line, and mic inputs  1U 19" rack-mountable, rugged steel chassis</p> <p><b>2 Cardioid condenser XLR microphone</b>  cardioid polar pattern  20-20,000 Hz freq response  -37 dB (14.1 mV) re 1V at 1 Pa open circuit sensitivity  100 ohms impedance  144 dB SPL, 1 kHz at 1% T.H.D. max input  124 dB, 1 kHz at Max SPL dynamic range  74 dB, 1 kHz at 1 Pa signal-to-noise ratio  XLR connector</p> <p><b>2 1-channel mic activator</b>  Channels: 1  Compatible Microphones: Dynamic, Ribbon, Powered Condenser**  Gain: +25dB  Connectors: XLR Input, XLR Output  Dimensions (DxWxH): 4.5" x 2.0" x 2.0"  Weight: 0.85 lb</p> <p><b>8 XLR male to female mic cables</b>  25 feet length  3-pin zinc alloy connectors  copper conductors  plug-and-play design</p> <p><b>2 Microphone stand with isolation shield and pop filter</b>  3 panel mic acoustic isolation shield  heavy duty stand, length up to 175 cm  metal thread adapter  pop filter  3/8-Inch Male to 5/8-Inch Mic Screw Adapter</p> <p><b>1 6-channel headphone amplifier</b>  6 auxilliary inputs  dual channel balance control  one front- and two rear-panel stereo 1/4" TRS headphone jacks on each channel</p> <p>Mono, Mute L, and Mute R select buttons  modes Stereo, Mono Left, Mono Right, and Mono Both (Left &amp; Right) on each channel  XLR and 1/4-inch TRS optional input</p>			



STOCK NO.	UNIT	DESCRIPTION	QTY	UNIT COST	TOTAL COST
		<p>with LED level metering on the main bus  four-segment indicators on each output channel  110 V power input/requirement  <b>2 5000 Watt Step Up/Down Voltage Transformer Converter Box with Built-in Voltage Regulator for 110V-240V</b>  5000 watt  Converts 110/120 volt to 220/240 V and Single Phase 220 volt to 110/120 volt AC 110v+-3% or Single Phase AC 220v+-3%. Compatible with 50 Hz and 60 Hz  Two Universal 220V outlet and Three 110V outlet  metal casing</p> <p><b>1 Digital audio workstation controller</b>  8+1 touch-sensitive motorized faders with 10-bit resolution  8 dual-function encoder knobs (rotate and enter)  Touch-Sensitive Master Fader  USB connector  12V2.5A DC  1.855kg (4.1lb)  15.6"(L) x 7.7"(W) x 2.3"(H)  Supports Most Major DAWs</p> <p><b>2 Snake cables</b>  25 feet length  8 x XLR sends (no returns)  8-channel sub  side-entry jacks</p> <p><b>2 2-Way Active Studio Monitor Speaker</b>  active studio monitor system  2-way configuration  6.5" kevlar aramid fiber woofer  1" kevlar aramid fiber tweeter  42Hz to 40kHz frequency response</p> <p><b>4 XLR Male to 1/4in TRS Male Cable</b>  10 ft length  XLR to 1/4 TRS  gold plated TRS</p> <p><b>4 over-the-ear studio monitor headphones</b>  45 mm driver  neodymium magnet  copper/clad aluminum wire voice coil  15 - 28,000 Hz frequency response  1,600 mW at 1 kHz max input power  99 dB sensitivity  38 ohms impedance  with 3-meter coiled detachable cable (with 6.35mm Male to 3.5mm Female Stereo Adapter)  90° swiveling earcups for easy, one-ear monitoring  Circumaural over-the-ear design</p>			

STOCK NO.	UNIT	DESCRIPTION	QTY	UNIT COST	TOTAL COST
		<p><b>5 Portable Solid State Drive</b>            Storage Capacity:1TB            Read Speed: Up to 550MB/s            Ruggedized, Water, and Dust-resistant (IP55-Rated)            Shock-resistant solid state core for greater durability            Shock-resistant: Up to 1500G and Vibration-resistant: 5g RMS, 10-2000 HZ            Non-Operating Temperature: from -20°C to 70°C, Operating temperature: from 0°C to 45°C            Compact and Pocket-sized            For PC and Mac users</p> <p><b>1 Rally Video Conferencing Kit with 1 Speaker and 1 Micpod</b>            Plug and play Rally Plus with any PC, Mac, or Chromebox via USB            Rally Camera Rally Display Hub Rally Table Hub Rally Speaker Rally Mic Pod            Remote control USB Type C to USB Type C USB Type A to USB Type B CAT6A            Ethernet cable HDMI Type A (x2) A/C cables (x2) Power Supplies (x2)            Documentation</p> <p>Studio quality video at resolutions up to 4K            Advanced modular audio that's crystal clear for premium video conferencing</p> <p>Sleek, industrial design created for today's modernwork spaces            Elevated user experience            Content sharing plus smart cabling</p> <p>Delivers studio-quality video, unmatched voice clarity, and RightSense automation for better meetings with video conferencing applications that work with USB devices, including Google Hangouts Meet, Microsoft Skype® for Business, Microsoft Teams, and Zoom. With modular audio, thoughtful cable management and premium finishes, Rally integrates beautifully into medium and larger rooms.</p> <p>Purpose:            For the establishment of studio set up for meetings, webinars and online briefings about agripreneurship and other related activities</p>	1	189,900.00	189,900.00

**TOTAL AMOUNT IN WORDS:**

**SEVEN HUNDRED EIGHTY FOUR THOUSAND FOUR HUNDRED EIGHTY PESOS ONLY**

₱ 784,480.00

In case of failure to make the full delivery within the time specified above, a penalty of one-tenth (1/10) of one percent (1%) for everyday of delay shall be imposed.

COMFORME:

*MARILYN N. NOZAKI*  
 \_\_\_\_\_  
 Signature Over Printed Name of Supplier  
 1/17/22  
 \_\_\_\_\_  
 Date

Very truly yours

*Rosana P. Mula*  
**ROSANA P. MULA, PhD**  
 OIC, DIRECTOR IV

FUNDS AVAILABLE:

**JOANE SINGSON**  
 CHIEF ACCOUNTANT

page 5 of 5

OR/BUR No.: 2021-12-48  
 12-23-21

Amount: Pnp. 784,480

BAC Secretariat Office

DEC 27 2021

pl 10:45